





TORICA®-aA / -aAY

| TECHNICAL INFORMATION | | |
|--|---|---|
| <p>TORIC MONOBLOC ACRYLIC ASPHERIC</p>   | <p>TORICA®-aA MC 6125 T</p>  | <p>TORICA®-aAY YELLOW MC 6125 T-Y</p>  |
| Type | foldable toric posterior chamber IOL one-piece with C-loop haptics | |
| Material | hydrophilic acrylic with UV absorber; water content 26% at 35° | |
| Specifics | toric meridional aspheric anterior surface (aberration free) ⁽²⁾ posterior surface with 360° lens epithelial cell barrier blue-light protection optional | |
| Diopter Range | <i>for more details on diopter categories, see page 2</i> | |
| Sphere in 0.5 D steps | -20.0 to 40.0 D | |
| Cylinder in 0.5 D steps | 1.0 to 25.0 D | |
| Cylinder Axis | the two thin diametrically opposed lines in the periphery of the optic indicate the axis of the plus-cylinder | |
| Est. A-const ⁽¹⁾ | 118.4 (optical biometry) | |

⁽¹⁾ For more details please visit www.humanoptics.com

⁽²⁾ The word "aberration" as used in this document refers to "spherical aberration"

DIOPTER CATEGORY - TORICA[®]-aA / -aAY

CYLINDER [D] →

